

PGDQ2.MH13881 - MARKING AND LABELING SYSTEMS - COMPONENT

Marking and Labeling Systems - Component

See General Information for Marking and Labeling Systems - Component

STAR LABEL PRODUCTS

42 NEWBOLD RD
FAIRLESS HILLS, PA 19030 USA

MH13881

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels, "Paper Label".						
ST-4						
	Alkyd paint	80	-	X(dry)	-	-
	Anodized aluminum	80	-	X(dry)	-	-
	Epoxy paint	80	-	X(dry)	-	-
	Polypropylene	80	-	X(dry)	-	-
Pressure-sensitive printed labels, "Polyester Label".						
ST-3						
	Aluminum	125	-40	X	X	F1, F2
	Alkyd paint	100	-40	X	X	F1, F2
	Galvanized steel	100	-40	X	X	F1, F2
	Stainless steel	100	-40	X	X	F1, F2
	Acrylonitrile butadiene styrene	80	-40	X	X	F1, F2
ST-7						
	Alkyd paint	150	-40	X	-	-
	Aluminum	150	-40	X	-	-
	Galvanized steel	150	-40	X	-	-
	Stainless steel	150	-40	X	-	-
	Polyurethane paint	100	-40	X	-	-

	Acrylonitrile butadiene styrene	80	-40	X	-	-
ST-9						
	Acrylic paint	150	-40	X	-	-
	Alkyd paint	150	-40	X	-	-
	Aluminum	150	-40	X	-	-
	Epoxy paint	150	-40	X	-	-
	Epoxy/Urethane powder paint	150	-40	X	-	-
	Galvanized steel	150	-40	X	-	-
	Polyester paint	150	-40	X	-	-
	Polyester powder paint	150	-40	X	-	-
	Polyvinyl fluoride	150	-40	X	-	-
	Stainless steel	150	-40	X	-	-
	Epoxy powder paint	125	-40	X	-	-
	Melamine	100	-40	X	-	-
	Nylon - Polyamide	100	-40	X	-	-
	Phenolic - Phenol Formaldehyde	100	-40	X	-	-
	Unsaturated polyester - thermoset	100	-40	X	-	-
	Acrylonitrile butadiene styrene	80	-40	X	-	-
	Polybutylene terephthalate	80	-40	X	-	-
	Polycarbonate	80	-40	X	-	-
	Polypropylene	80	-	X	-	-
	Polystyrene	80	-40	X	-	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

F1 - Occasional exposure to Fuel Oil No. 1.

F2 - Occasional exposure to Fuel Oil No. 2.

Marking: Company name and model designation.

Last Updated on 2016-04-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"